



Torx Bit, T40

NOTE: Right and Left side of Motorcycle is determined while sitting on the bike.

PARTS LIST

Your kit contains 1 Left or 1 Right Frame Bag.

PREPARATION

1. Position the motorcycle securely on its side stand.
2. Before installing your frame bag(s) apply a high quality leather dressing / water repellent product to protect the leather from moisture and dirt.

INSTALLATION

1. Remove the two screws from the passenger peg mounting bracket (Torx Bit). The bracket will be freed from the motorcycle frame.
2. Position the Frame Bag so the holes in the mount bracket align with the passenger peg mounting holes.
3. Position the passenger peg mounting bracket outside the Frame Bag mounting bracket and thread the original screws through the passenger peg mounting bracket, the Frame Bag mounting bracket, and then into the threaded holes in the frame.
4. Tighten the screws to 20Nm (15 ft lbs)

MAINTENANCE

Before installing your frame bag(s) apply a high quality leather dressing / water repellent product to protect the leather from moisture and dirt.

Periodically clean your frame bags with a quality leather cleaner / conditioner product. Follow the cleaning with an application of a leather dressing/ water repellent product to protect the leather from moisture.

Products available through motorcycle dealers are:

- LEXOL® Leather Cleaner
- LEXOL® Leather Conditioner
- IFW Leather Cleaner/ Conditioner
- IFW Leather Water Repellent

