

# Installation Instructions

MOTORCYCLE ACCESSORIES



R1200 C EURO Light O-ring Upgrade Kit

Part Number 99-99-0-000-008

This kit is an upgrade to insure that moisture does not enter into the lamp housing.

**Tools Required:** None

The following symbols are used in these instructions for safety notes:

**Attention:**



Special notes and cautionary measures which can prevent damage to the motorcycle. Failure to observe these can result in nullification of the warranty.


**Note:**



Tips for facilitation of operation, control and adjustment, as well as maintenance work.

Parts list:		
Qty.	Description	Part No.
2	O-rings	
1	Packet silicone grease	

1. Unscrew the lamp bezel.
2. Remove the silicone flat gasket (orange) and clear glass lens from the bezel. Place in a clean non-abrasive location.
3. Remove the O-ring from the bezel and discard.
4. Apply silicone grease to the replacement O-ring (enough to coat the entire O-ring) and place in the bezel. Insure that the O-ring is in the O-ring groove.
5. Clean your hands.
6. Clean the lens.
7. Replace the lens and the silicone gasket in the order that they came out of the bezel: bezel, O-ring, glass lens, silicone gasket.
8. Carefully screw the bezel back onto the lamp housing.

**Attention:**  9. **DO NOT OVER TIGHTEN.** Tighten only enough to insure that the lens does not rattle or move. Over tightening will cause lamp failure. There should now be a small gap where the bezel and the lamp housing come together.

10. Clean the lens and lamp assembly with a soft, clean cloth.
11. Repeat for second lamp.

